

18
YEARS
OF EXCELLENCE

LET LIFE **FLOW!**

flowconME

www.flowconme.com

PREFACE

flowconME has been at the forefront of fluid technology since its inception in 2004.

We offer a wide range of valves, including both Manual and Electrical, under stringent quality control as per ISO 9001:2015. The sizes we offer are from 15mm to over 2000mm. We diligently work with our clients to define the proper fit for their purposes to help them heighten their output. Whether using our standard valve offerings, or something more customized with a touch of sophistication, our team can help you find the best fit.

With own manufacturing facilities in Italy we are specialized in chilled water and plumbing applications, the utilization of our products in various forms is possible with the addition of special material requirements.

From valves to piping, flowconME has inventory available in different regions to get to your worksite, whether from Italy or Dubai, on a quicker delivery basis. Our rigorous quality control process covers each step of the manufacturing process, from design to aftermarket assistance. Let our team assist you in mapping out your project. Not only is flowconME a manufacturer, but we are also a complete turnkey provider for several industries. Our team of experienced personnel will be there to assist you at every step. Our technical team has a broad range of industry experience and will be with you every step of the process. The after sales support staff is ready to help with any aspects of the project once the sale is complete. They are incredibly dedicated and experienced in the field.

- Technical and aftersales support has extensive, in-depth experience.
- Our projects range across Europe, GCC, and Africa
- From concept throughout manufacturing, we develop every stage.

The manufacturing facilities in Italy offers foundry, machining facilities, test facilities, and warehouse. The warehouse has dedicated storage, packaging, and logistics onsite.

Our catalogue has vast selection of water service and HVAC valves, and accessories to meet your needs for your systems.

We have full range of WRAS approved valves **flowIT** brand catering to the potable under water applications.

Chiller Plant, Distribution and ETS room components are available as well.

We provide exceptional quality expansion joints and flexible connectors of different materials to fit any project. flowconME focuses on delivering excellent products from the concept stage throughout the entire development process.

flowconME has extensive distribution channels of our own, as well as channels through our distribution partners, which provides us the ability to ensure delivery and service of our products in an extremely efficient timeframe. Contact us today to get started designing, manufacturing, and delivering the highest quality components for YOU.



GATE VALVES

NON-RISING STEM

Fig. FTBGDW-16



Size	: DN15 - DN50
Pressure	: PN16
Body	: DZR Brass
Ends	: Threaded (BS EN 10226-2)



NON-RISING STEM

Fig. FLBG-20

Size	: DN15 - DN50
Pressure	: PN20
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



NON-RISING STEM - LOCK-SHIELD

Fig. FLBG-20LS

Size	: DN15 - DN50
Pressure	: PN20
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



NON-RISING STEM

Fig. FTBGW-20



Size	: DN15 - DN50
Pressure	: PN20
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



NON-RISING STEM

Fig. FLBG-20S

Size	: DN15 - DN50
Pressure	: PN20
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



NON-RISING STEM - LOCK-SHIELD

Fig. FLBG-20SLS

Size	: DN15 - DN50
Pressure	: PN20
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



NON-RISING STEM

Fig. FTBGW-20S



Size	: DN15 - DN50
Pressure	: PN20
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



RISING STEM

Fig. FLBG-20RS

Size	: DN15 - DN50
Pressure	: PN20
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



NON-RISING STEM

Fig. FLBG-25C

Size	: DN15 - DN50
Pressure	: PN25
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



RISING STEM

Fig. FLBG-32RS

Size	: DN15 - DN50
Pressure	: PN32
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



GATE VALVES

NON-RISING STEM, METAL SEATED

Fig. FLIG-16

Size	: DN65 - DN400
Pressure	: PN16
Body	: Cast Iron
Ends	: Flanged (BS EN 1092-2)



RISING STEM, METAL SEATED

Fig. FLIG-16RS

Size	: DN65 - DN300
Pressure	: PN16
Body	: Cast Iron
Ends	: Flanged (BS EN 1092-2)



NON-RISING STEM - RESILIENT SEATED

Fig. FLRIG-16

Size	: DN65 - DN600
Pressure	: PN16
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



NON-RISING STEM - RESILIENT SEATED

Fig. FLRIG-25

Size	: DN65 - DN300
Pressure	: PN25
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



NON-RISING STEM - RESILIENT SEATED

Fig. FTRIGW-16



Size	: DN65 - DN600
Pressure	: PN16
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



NON-RISING STEM - RESILIENT SEATED

Fig. FTRIGW-25



Size	: DN65 - DN300
Pressure	: PN25
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



BALL VALVES

FULL BORE, LEVER TYPE

Fig. FLBL-25

Size	: DN15 - DN50
Pressure	: PN25
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



FULL BORE, LEVER TYPE

Fig. FTBLW-25



Size	: DN15 - DN50
Pressure	: PN25
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



FULL BORE, LEVER TYPE

Fig. FLBRSL-25

Size	: DN15 - DN50
Pressure	: PN25
Body	: DZR Brass
Ends	: Threaded (BS EN 10226-2)



FULL BORE, LEVER TYPE, EXTENDED STEM

Fig. FLBRSL-25EXT

Size	: DN15 - DN50
Pressure	: PN25
Body	: DZR Brass
Ends	: Threaded (BS EN 10226-2)



BUTTERFLY VALVES

SEMI-LUGGED, WAFER PATTERN

Fig. FLBL-160 & FLBG-160

Size	: DN65 - DN600
Pressure	: PN16
Body	: Ductile Iron
Ends	: Wafer (BS EN 1092)



SEMI-LUGGED, WAFER PATTERN

Fig. FTBW-250-PN16

Size	: DN65 - DN300
Pressure	: PN16
Body	: Ductile Iron
Ends	: Wafer (BS EN 1092)



FULLY-LUGGED, WAFER PATTERN

Fig. FLBL-161 & FLBG-161


Size	: DN65 - DN600
Pressure	: PN16
Body	: Ductile Iron
Ends	: Wafer (BS EN 1092-2)



FULLY-LUGGED, WAFER PATTERN

Fig. FTBW-251-PN16


Size	: DN65 - DN600
Pressure	: PN16
Body	: Ductile Iron
Ends	: Wafer (BS EN 1092-2)



FULLY-LUGGED, WAFER PATTERN

Fig. FLBL-251 & FLBG-251


Size	: DN65 - DN600
Pressure	: PN25
Body	: Ductile Iron
Ends	: Wafer (BS EN 1092-2)



FULLY-LUGGED, WAFER PATTERN

Fig. FTBW-251-PN25

Size	: DN65 - DN600
Pressure	: PN25
Body	: Ductile Iron
Ends	: Wafer (BS EN 1092-2)



DOUBLE FLANGED

Fig. FLDFB-161

Size	: DN700 - DN1000
Pressure	: PN16
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



ELECTRIC ACTUATORS

Fig. FL4 Series

Torque	: 100-3000Nm
Type	: On/Off or Modulating
Size	: Butterfly Valve DN65 - DN500
Pressure	: Butterfly Valve PN16-25



DOUBLE ECCENTRIC, DOUBLE FLANGED

Fig. FLDFEB-D Series

Size	: DN100 - DN1500
Pressure	: PN10-16-25-40
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



METAL SEATED, DOUBLE FLANGED

Fig. FLCBL Series

Size	: DN80 - DN1300
Pressure	: PN10-16-25-40
Body	: WCB
Ends	: Flanged



GLOBE VALVES

RISING STEM, THREADED

Fig. FLBGL-16

Size	: DN15 - DN50
Pressure	: PN16
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



RISING STEM, FLANGED

Fig. FLIGL-16

Size	: DN65 - DN300
Pressure	: PN16
Body	: Cast Iron
Ends	: Flanged (BS EN 1092-2)



DOUBLE REGULATING VALVES

GLOBE PATTERN, FIXED ORIFICE

Fig. FLFO-25

Size	: DN15 - DN50
Pressure	: PN25
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



GLOBE PATTERN, FIXED ORIFICE

Fig. FTFO-25

Size	: DN15 - DN50
Pressure	: PN25
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



GLOBE PATTERN, FIXED ORIFICE

Fig. FL100-21FO

Size	: DN65 - DN300
Pressure	: PN16
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



GLOBE PATTERN, FIXED ORIFICE

Fig. FL100-25FO

Size	: DN65 - DN300
Pressure	: PN25
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



ORIFICE PLATES & TEST POINTS

THREADED, WITH TEST POINTS

Fig. FLMMAM-20

Size	: DN15 - DN50
Pressure	: PN20
Body	: DZR Brass
Ends	: Threaded (BS EN 10226-2)



WAFER TYPE, WITH TEST POINTS

Fig. FLSSM-16


Size	: DN65 - DN600
Pressure	: PN16
Body	: Stainless Steel
Ends	: Wafer (BS EN 1092)



WAFER TYPE, WITH TEST POINTS

Fig. FLSSM-25

Size	: DN65 - DN600
Pressure	: PN25
Body	: Stainless Steel
Ends	: Wafer (BS EN 1092)



TEST POINTS

Fig. FLTP

Size	: ¼"
Pressure	: PN25
Body	: DZR Brass
Ends	: Threaded (BS EN 10226-2)



FCU LINK FOR PICV SYSTEM

FCU VALVE PACKAGE

Fig. FTFCU Series

Size	: DN15 - DN32
Pressure	: PN20-25
Body	: DZR Brass
Ends	: Threaded (BS EN 10226-2)



FCU VALVE PACKAGE w. INSULATION BOX

Fig. FTFCU Series

Size	: DN15 - DN32
Pressure	: PN20-25
Body	: DZR Brass
Ends	: Threaded (BS EN 10226-2)



AIR VALVES

THREADED COVER, PP FLOAT

Fig. FLAV

Size	: DN15 - DN25
Pressure	: PN16
Body	: Brass
Ends	: Threaded (BS EN 10226-2)



THREADED COVER, PP FLOAT

Fig. FTBRZAVW-10



Size	: DN15 - DN25
Pressure	: PN10
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



THREADED COVER, SS FLOAT

Fig. FLBRZAV-12HT

Size	: DN15 - DN25
Pressure	: PN12
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



THREADED COVER, SS FLOAT

Fig. FTBRZAVW-12



Size	: DN15 - DN25
Pressure	: PN12
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



SINGLE CHAMBER, SINGLE FUNCTION

Fig. FLARV-SCSF-D Series

Size	: DN25
Pressure	: PN10-16-25-40
Body	: Ductile Iron
End	: Threaded



DOUBLE CHAMBER, TRIPLE FUNCTION

Fig. FLARV-DCTF-D Series

Size	: DN40 - DN500
Pressure	: PN10-16-25-40
Body	: Ductile Iron
End	: Flanged (BS EN 1092-2)



CHECK VALVES

SWING PATTERN

Fig. FLBCK-20

Size	: DN15 - DN50
Pressure	: PN20
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



SWING PATTERN

Fig. FTBCW-20



Size	: DN15 - DN50
Pressure	: PN20
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



CHECK VALVES

SWING PATTERN

Fig. FLSCK-16

Size	: DN65 - DN600
Pressure	: PN16
Body	: Cast Iron
Ends	: Flanged (BS EN 1092-2)



SWING PATTERN

Fig. FLSCK-25

Size	: DN65 - DN300
Pressure	: PN25
Body	: Cast Iron
Ends	: Flanged (BS EN 1092-2)



SWING PATTERN, LEVER & WEIGHT

Fig. FLSCK-16LW

Size	: DN65 - DN600
Pressure	: PN16
Body	: Cast Iron
Ends	: Flanged (BS EN 1092-2)



SWING PATTERN, LEVER & WEIGHT

Fig. FLSCK-25LW

Size	: DN65 - DN600
Pressure	: PN25
Body	: Cast Iron
Ends	: Flanged (BS EN 1092-2)



SWING PATTERN, AIR CUSHIONED

Fig. FLSCK-16AC

Size	: DN65 - DN600
Pressure	: PN16
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



WAFER TYPE, SPRING LOADED

Fig. FLDDCK-16

Size	: DN65 - DN600
Pressure	: PN16
Body	: Cast Iron
Ends	: Wafer (BS EN 1092)



WAFER TYPE, SPRING LOADED

Fig. FTDDCW-16

Size	: DN65 - DN600
Pressure	: PN16
Body	: Cast Iron
Ends	: Wafer (BS EN 1092)



WAFER TYPE, SPRING LOADED

Fig. FLDDCK-25

Size	: DN65 - DN600
Pressure	: PN25
Body	: Cast Iron
Ends	: Wafer (BS EN 1092)



WAFER TYPE, SPRING LOADED

Fig. FTDDCW-25

Size	: DN65 - DN600
Pressure	: PN25
Body	: Cast Iron
Ends	: Wafer (BS EN 1092)



SILENT TYPE, SPRING LOADED

Fig. FLSCV-D Series

Size	: DN65 - DN1000
Pressure	: PN10-16-25-40
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



CONTROL VALVES

SOLENOID CONTROL VALVE

Fig. FLCV-SL-D Series

Size	: DN40 - DN400
Pressure	: PN10-16-25-40
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



PRESSURE REDUCING VALVE

Fig. FLCV-PR-D Series

Size	: DN40 - DN400
Pressure	: PN10-16-25-40
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



PRESSURE RELIEF / SUSTAINING VALVE

Fig. FLCV-PS-D Series

Size	: DN40 - DN400
Pressure	: PN10-16-25-40
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



QUICK PRESSURE RELIEF VALVE

Fig. FLCV-QR-D Series

Size	: DN40 - DN400
Pressure	: PN10-16-25-40
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



SURGE ANTICIPATING VALVE

Fig. FLCV-SA-D Series

Size	: DN40 - DN400
Pressure	: PN10-16-25-40
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



BOOSTER PUMP CONTROL VALVE

Fig. FLCV-PC-D Series

Size	: DN40 - DN400
Pressure	: PN10-16-25-40
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



LEVEL CONTROL VALVE

Fig. FLCV-LC-D Series

Size	: DN40 - DN400
Pressure	: PN10-16-25-40
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



FLOW CONTROL VALVE

Fig. FLCV-FC-D Series

Size	: DN40 - DN400
Pressure	: PN10-16-25-40
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



OTHER VALVES & ACCESSORIES

DRAIN COCKS

Fig. FLDC

Size	: DN15 - DN25
Pressure	: PN16
Body	: DZR Brass
Ends	: Threaded (BS EN 10226-2)



BIB TAPS, BALL TYPE

Fig. FLHB-1320

Size	: DN15 - DN20
Pressure	: PN16
Body	: Brass
Ends	: Threaded (BS EN 10226-2)



OTHER VALVES & ACCESSORIES

VACUUM BREAKER

Fig. FLVB

Size	: DN20
Pressure	: PN12
Body	: Brass
Ends	: ¾" BSPP



ANGLE VALVE

Fig. FLBAV-16

Size	: DN15
Pressure	: PN16
Body	: Chrome Plated Brass
Ends	: ½" BSPP



FOOT VALVE WITH STRAINER

Fig. FLBRFVSS-10C

Size	: DN15 - DN100
Pressure	: PN10
Body	: Brass
Ends	: Threaded (BS EN 10226-2)



FOOT VALVE WITH STRAINER

Fig. FLFTV-D Series

Size	: DN50 - DN400
Pressure	: PN10-16
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



PRESSURE REDUCING VALVES

Fig. FTBPRVW-20

Size	: DN15 - DN100
Pressure	: PN20
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



PRESSURE REDUCING VALVES

Fig. FLIPRV-16G

Size	: DN50 - DN300
Pressure	: PN16
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



DISMANTLING JOINTS

Fig. FLIDJ-D Series

Size	: DN80 - DN1500
Pressure	: PN10-16-25-40
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



TRIPLE DUTY VALVE - STRAIGHT TYPE

Fig. FLTDV38-SR Series

Size	: DN65 - DN300
Pressure	: PN16-25
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



TRIPLE DUTY VALVE - ANGLE TYPE

Fig. FLTDV39-16SR

Size	: DN65 - DN300
Pressure	: PN16
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



TRIPLE DUTY VALVE - STRAIGHT TYPE

Fig. FLTDV40-16SR

Size	: DN65 - DN300
Pressure	: PN16
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



STRAINERS & SUCTION DIFFUSERS

Y STRAINER, SCREWED CAP

Fig. FLBS-20

Size	: DN15 - DN50
Pressure	: PN20
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



Y STRAINER, SCREWED CAP

Fig. FTBSW-20



Size	: DN15 - DN50
Pressure	: PN20
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



Y STRAINER, SCREWED CAP

Fig. FLBS-25

Size	: DN15 - DN50
Pressure	: PN25
Body	: Bronze
Ends	: Threaded (BS EN 10226-2)



Y STRAINER, BOLTED BONNET

Fig. FLIS-16

Size	: DN65 - DN600
Pressure	: PN16
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



Y STRAINER, BOLTED BONNET

Fig. FTISW-16



Size	: DN65 - DN600
Pressure	: PN16
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



Y STRAINER, BOLTED BONNET

Fig. FLIS-25

Size	: DN65 - DN600
Pressure	: PN25
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



Y STRAINER, BOLTED BONNET

Fig. FTISW-25



Size	: DN65 - DN600
Pressure	: PN25
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



BASKET STRAINER

Fig. FLIBS-D Series

Size	: DN65 - DN1600
Pressure	: PN10-16-25-40
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



SUCTION DIFFUSER

Fig. FLISD-16

Size	: DN65 - DN400
Pressure	: PN16
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



SUCTION DIFFUSER

Fig. FLISD-25SW

Size	: DN65 - DN600
Pressure	: PN25
Body	: Cast Steel
Ends	: Flanged (BS EN 1092-1)



FLEXIBLE CONNECTORS

CORRUGATED BELLOW TYPE

Fig. FLFH-20BE

Size	: DN15 - DN32
Pressure	: PN20
Body	: Stainless Steel
Ends	: Threaded (BS EN 10226-2)



CORRUGATED BELLOW, BRAIDED TYPE

Fig. FLFH-25

Size	: DN15 - DN32
Pressure	: PN25
Body	: Stainless Steel
Ends	: Threaded (BS EN 10226-2)



EPDM DOUBLE SPHERE

Fig. FLUC-16

Size	: DN15 - DN50
Pressure	: PN16
Body	: EPDM
Ends	: Threaded (BS EN 10226-2)



EPDM DOUBLE SPHERE, LIMIT WIRE

Fig. FLUC-16LW

Size	: DN15 - DN50
Pressure	: PN16
Body	: EPDM
Ends	: Threaded (BS EN 10226-2)



EPDM DOUBLE SPHERE, LIMIT WIRE

Fig. FLUC-25LW

Size	: DN15 - DN50
Pressure	: PN25
Body	: EPDM
Ends	: Threaded (BS EN 10226-2)



EPDM SINGLE SPHERE

Fig. FLFC-16

Size	: DN65 - DN300
Pressure	: PN16
Body	: EPDM
Ends	: Flanged (BS EN 1092-2)



EPDM SINGLE SPHERE, CONTROL RODS

Fig. FLFC-16CR

Size	: DN65 - DN600
Pressure	: PN16
Body	: EPDM
Ends	: Flanged (BS EN 1092-2)



EPDM SINGLE SPHERE, CONTROL RODS

Fig. FLFC-25CR

Size	: DN65 - DN600
Pressure	: PN25
Body	: EPDM
Ends	: Flanged (BS EN 1092-2)



EPDM DOUBLE SPHERE

Fig. FLFC-16DB

Size	: DN65 - DN600
Pressure	: PN16
Body	: EPDM
Ends	: Flanged (BS EN 1092-2)



EPDM DOUBLE SPHERE

Fig. FLFC-25DB

Size	: DN65 - DN300
Pressure	: PN25
Body	: EPDM
Ends	: Flanged (BS EN 1092-2)



OTHER VALVES

FLANGED BALL VALVES

FLOATING TYPE


Size	: DN15 - DN250
Pressure	: PN16/PN25
Body	: Cast Iron / Ductile Iron
Ends	: Flanged (BS EN 1092-2)



WAFER TYPE BALL VALVES

FLOATING TYPE


Size	: DN20 - DN100
Pressure	: PN16/PN25
Body	: Cast iron/ Ductile iron
Ends	: Flanged (BS EN1092-2)



FLANGED BALL VALVES

BRONZE

Size	: DN15 - DN250
Pressure	: PN16
Body	: Bronze
Ends	: Flanged



GATE VALVE

Size	: DN40 - DN300
Pressure	: PN16/PN25
Body	: Cast Iron / Ductile Iron
Ends	: Flanged (BS EN 1092-2)



MOTORIZED GATE VALVES

Size	: DN40 - DN300
Pressure	: PN16/PN
Body	: Cast Iron / Ductile Iron
Ends	: Flanged (BS EN 1092-2)



GATE VALVE

SOFT SEATED, NBR/EPDM

Size	: DN40 - DN300
Pressure	: PN16/PN25
Body	: Cast Iron / Ductile Iron
Ends	: Flanged (BS EN 1092-2)



METAL SEATED GATE VALVES

NON-RISING STEM

Size	: DN50 - DN600
Pressure	: PN16/PN25
Body	: Cast Iron / Ductile Iron
Ends	: Flanged (BS EN 1092-2)



KNIFE GATE VALVE

RISING STEM, BI-DIRECTIONAL

Size	: DN50 - DN600
Pressure	: PN16/PN25
Body	: Cast Iron / Ductile Iron
Ends	: Flanged (BS EN 1092-2)



NEEDLE VALVE

SERIES 14

Size	: DN80 - DN600
Pressure	: Up to 64 bar
Body	: Ductile Iron
Ends	: Wafer (BS EN 1092-2)



DIAPHRAGM OR PISTON CONTROL VALVE

PILOT OPERATED

Size	: DN65 - DN400
Pressure	: PN10/PN16/PN25
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



OTHER VALVES

VENTURI CHECK VALVE

SERIES M16

Size	: DN65 - DN600
Pressure	: PN10/PN16
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



STRAINER BASKETS

Size	: DN60 - DN300
Pressure	:
Body	: Stainless Steel
Ends	: Flanged (PN10/PN16)



BALL CHECK VALVE

THREADED

Size	: DN15 - DN80
Pressure	: PN16/PN25
Body	: Cast Iron / Ductile Iron
Ends	: Threaded ends



BALL CHECK VALVE

FLANGED

Size	: DN50 - DN250
Pressure	: PN16
Body	: Cast Iron / Ductile Iron
Ends	: Flanged (BS EN 1092-2)



SWING CHECK VALVES

WAFFER TYPE

Size	: DN50 - DN600
Pressure	: PN16/PN25
Body	: SS / Cast Iron / Ductile Iron
Ends	: Wafer (BS EN 1092)



WAFFER CHECK VALVES

SPRING TYPE

Size	: DN50 - DN600
Pressure	: PN16/PN25
Body	: Cast Iron / Ductile Iron
Ends	: Wafer (BS EN 1092-2)



SPRING CHECK VALVES

THREADED

Size	: DN15 - DN50
Pressure	: PN16
Body	: Cast Iron / Ductile Iron
Ends	: Threaded



SPRING CHECK VALVES

FLANGED

Size	: DN50 - DN600
Pressure	: PN16/PN25
Body	: Cast Iron / Ductile Iron
Ends	: Flanged (BS EN 1092-2)



TILTING CHECK VALVES

FLANGED

Size	: DN80 - DN600
Pressure	: PN10/PN16
Body	: Ductile Iron
Ends	: Flanged (BS EN 1092-2)



Y CHECK VALVE WITH SPRING

THREADED

Size	: DN15 - DN50
Pressure	: PN40
Body	: Stainless steel
Ends	: Threaded



flowconME s.r.l., Via Cesare Battisti 2, Bologna, Italy
Production / Warehouse: Poggiorsini, Bari, Italy
Phone: +39 051 0827134, Email: info@flowconme.com
Web Site: www.flowconme.com

flowconME

flowIT