

White PE Insulation

Type A Set – White
Standard Plain End Line



Type B Set – White
Mini-Split Twin Tube (Joined)



Type C Set – White
Mini-Split (Separate)



Type D Set – White
Insulated Copper Tube (Single Line)



Type E Set – White
Plain End Fully Assembled (Taped)



Type E Set – White with Thermostat Wire
Standard Plain End Line



Black PE Insulation

Type A Set – Black
Standard Plain End Line



Type B Set – Black
Mini-Split Twin Tube (Joined)



Type C Set – Black
Mini-Split (Separate)



Type D Set – Black
Insulated Copper Tube (Single Line)



Type E Set – Black
Plain End Fully Assembled (Taped)



Black Rubber Insulation

Type F Set

Standard Plain End Line



Type G Set

Mini-Split (Separate)



Type H Piece

Insulated Copper Tube (Single Line)



Type I Set

Plain End Fully Assembled (Taped)



Type I Set – Black with Thermostat Wire

Plain End Fully Assembled (Taped)



Cool Pull Mini Line Set Kits

ICOOL split line set kits consist of annealed copper tube with a high quality insulation layer (M1 certified) widely used for the insulation of split air conditioners and refrigerant equipment.

Copper tubes are produced according to ASTM B280 or B743 with the temper of soft annealed. All kits are suitable for R410a refrigerant and other high-pressure refrigerant.

Insulation layer is made of cross-lined foam polyethylene with closed cells. The insulation is covered with embossed polyethylene film to prevent the foam from creasing.

Fire retardant and UV resistance
 Heating conduction at 0°C, ≤ 0.033 W/mk
 Average Density: 33KG/m³
 Working temperature from -40°F to +300°F
 Vapor resistance: $\mu > 5000$
 White/external non-toxic and resistant to external chemical agents and ultra-violet rays.

Mini Split Line Set Accessories

Accessories consist of all components needed for air conditioner installation.

1. Drain hose
2. Non-adhesive PVC tape
3. Electrical wire (TC-ER 4/16 AW / 4/14 AWG)
4. Seal mud (150g to 200g)
5. Wall sleeve kits (PVC sleeve cover and wall corner)

Packing

COPPER TUBE SIZE	AIR CONDITIONER CAPACITIES
1/4" and 3/8"	9000 BTU
1/4" and 1/2"	12000 BTU and 18000 BTU
1/4" and 5/8"	24000 BTU and 28000 BTU
3/8" and 5/8"	36000 BTU inverter

*Standard lengths:

50 ft and 100 ft

*Customized lengths:

10 ft to 164 ft

